



V-PRO is available in more than 29 countries distributors of covering materials used in the construction industry. Our success is based on in-depth knowledge, professionalism and customer focus. V-PRO is available in more than 29 countries.

Description

V-PRO Protection Board is temporary floor protection made out of misprints from juice box packaging / milk cartons. The material consists of 2 sides double laminated paper. V-PRO is waterproof, easy to apply and remove, perfect for use during activities such as painting, stucco applications, remodeling, moving, etc. Besides that, it is the most sustainable option to protect your floor. V-PRO Protection Board is an exclusive product of Verbo, used by professionals and consumers. Simply lay the roll on the floor and kick it out to the desired length. It doesn't get much easier.

Technical Service

Verbo focuses on long-term relationships so that a partnership is created. To realize this and achieve more together, we can do the following for you: supplying commercial product information and product photos. Providing technical product specifications. Helping present your product both physically and online. An open door policy with honest and fast communication. Thinking along with your specific customer requests, personally, by email or by telephone.

Phone: +31 (0) 13 463 25 55
Email: sales@v-procover.com
Website: www.v-procover.com



Availability

V-PRO is part of Verbo which is one of Europe's leading manufacturers and Our success is based on in-depth knowledge, professionalism and customer focus.

Specifications

Available in: 538sq.ft. Width: \pm 51 inch. Fleece weight: 33lbs per roll. Coated: Coated on both sides. Waterproof: yes.

V-PRO is delivered in roll form and lays out fast making it quick and easy to install. It provides the following advantages: Heavy-duty, non-staining, FSC® certified, lays out fast, waterproof, Proudly made in the Netherlands.



V-PRO tape

The tape we recommend when using the Protection Board is the V-PRO tape. This tape is very easy to pull off the roll and has a high dimensional stability. It is also very flexible and adapts very well to the surface.

Suitable for: Smooth metals and flat and polished surfaces like most plastics, varnished wood, paints and lacquers.

Not suitable for: Subfloors with insufficient internal stability such as poorly adhering varnish or weathered wood. 100% compatibility with the substrate can only be guaranteed by first carrying out a test for at least 48 hours under the conditions of use and the correct way of working.

Our Process

See our process from juice box packaging / milk cartons to Protection Board below.

